



NOTES

1. GUIDE RAILS ARE REQUIRED ON FILLS 3 m IN HEIGHT OR MORE. WHERE STEEL BEAM GUIDE RAIL IS INDICATED WIDTH OF ROUNDING SHALL BE 1 m.
2. WIDTH OF DRIVEWAY TAPERS FROM END OF RADIUS TO MEET EXISTING DRIVEWAY.
3. DRIVEWAY WIDTH VARIES - MINIMUM 3 m, MAXIMUM 6.1 m.
4. SLOPES: FOR HEIGHTS OF FILL OR DEPTHS OF CUT 1 m OR LESS, USE 3:1 SLOPE.
FOR HEIGHTS OF FILL OR DEPTHS OF CUT OVER 1 m, USE A 2:1 SLOPE.
5. ALL DIMENSIONS ARE IN METRES UNLESS OTHERWISE SHOWN.



**TYPICAL URBAN
PRIVATE ENTRANCE WITH
BOULEVARD & SIDEWALK**

DRAWN BY: STS/RFRANK	REV No:
DATE: 2003-03-03	REV DATE:
SCALE: NTS	CAD/FILE No.: A1925-1 (1 OF 1)
APP'D:	GSSD-303.020

DISCLAIMER OF WARRANTY : The data is provided "as-is", without warranty of any kind either expressed or implied. Any and all liabilities for damage, direct or indirect, however caused, and resulting in any way by use of the supplied data is the full and final responsibility of the user.

COPYRIGHT : All rights are reserved. No part of the supplied data may be reproduced, or transmitted to others, in any form or by any means, without the prior written permission of the CITY OF GREATER SUDBURY.