



NOTES:

1. MINIMUM DIMENSIONS ARE INDICATED. MAXIMUM DIMENSIONS AS PER SITE REQUIREMENTS.
2. PAVEMENT AND SIDEWALK STRUCTURE AT ENTRANCES SHALL BE CONSTRUCTED USING MATERIALS AND THICKNESSES AS SPECIFIED ELSEWHERE.
3. THIS STANDARD DOES NOT APPLY TO SIGNALIZED ENTRANCES.
4. THE DEPRESSED CURB THROUGH THE SIDE ENTRANCE SHALL BE A STRAIGHT VEE AND SHALL NOT INCORPORATE THE 25mm LIP.
5. FOR SIDEWALK RAMP AND TACTILE WARNING SURFACE SEE GSSD-310.033.
6. ZEBRA STRIPES TO BE 0.6m THICK O/S 1.25m.
7. FOR SIDEWALK DETAIL SEE GSSD-310.010.
8. WHERE SIDEWALK DOESN'T EXIST A 0.45m WIDE STOP BAR SHALL BE INSTALLED ALONG THE WIDTH OF THE OUTBOUND LANE LOCATED 1.0m FROM THE BACK OF THE CURB.



URBAN INDUSTRIAL,  
COMMERCIAL, INSTITUTIONAL &  
APARTMENT ENTRANCES

|                      |                                   |
|----------------------|-----------------------------------|
| DRAWN BY: RF/BWK/KLR | REV No: 2                         |
| DATE: 2003-03-03     | REV DATE: 2019-03-01              |
| SCALE: NTS           | CAD/FILE No.:<br>A1950-1 (1 OF 1) |
| APP'D: M. FRAYNE     | <b>GSSD-350.010</b>               |

DISCLAIMER OF WARRANTY : The data is provided "as-is", without warranty of any kind either expressed or implied. Any and all liabilities for damage, direct or indirect, however caused, and resulting in any way by use of the supplied data is the full and final responsibility of the user.

COPYRIGHT : All rights are reserved. No part of the supplied data may be reproduced, or transmitted to others, in any form or by any means, without the prior written permission of the CITY OF GREATER SUDBURY.